










Technical References – Targets only, without tolerances mentioned

	Whiteness	Opacity	Moisture	Bendtsen Roughness	Thickness	Bulk	Certified by
	CIE	%	%	ml/min	µm	µm/g/m ²	
	ISO 11475	ISO 2471	ISO 287	ISO 8791/2	ISO 534	—	—
80 g/m² Elite	171	94,5	4,0	160	108	1,35	
90 g/m² Elite Colour	171	95,5	4,0	140	119	1,32	
100 g/m² Elite Colour Plus	171	96,0	4,5	140	123	1,23	
110 g/m² Elite Colour Supreme	171	97,0	4,5	120	134	1,22	
160 g/m² Elite Colour Extreme	171	97,5 (minimum)	5,4	150	190	1,19	-
75 g/m² Office	161	92	4,0	220	106	1,33	
80 g/m² Office	160	93	4,0	200	107	1,34	
80 g/m² Fusion	163	93,0	4,0	250	111	1,39	

Additional Information about grupo Portucel Soporcel Mills and Products:

grupo Portucel Soporcel mills are chain-of-custody certified by the Smartwood Program of the Rainforest Alliance in accordance with FSC-STD-40-004 (SW-COC-1783 for Soporcel and SW-COC-1829 for Portucel).

In accordance with the requirements of ISO 9706 standard - Archival life over 200 years

Elemental Chlorine Free (ECF)

Quality Standard ISO 9001

Environmental Standard ISO 14001

Occupational Health and Safety Standard OHSAS 18001